Surpassing Performance Surpassing Performance

Superior Reagents, Quality Controls and Calibrators

High quality original reagents, calibrators and controls offer a complete system for our users. Cyanide free reagents allow laboratories to meet necessary environmental regulations. Complete traceability system ensures closest consistency with standard methods.





High Quality Design

New internal structural design separates electronic components from the fluidic system, decreasing interference while at the same time allowing for easier maintenance.



BC-3600

Auto Hematology Analyzer

Technical Specifications

Parameters

WBC, Lymph#, Mid#, Gran#, Lymph%, Mid%, Gran%, RBC, HGB, HCT, MCV, MCH, MCHC, RDW, PLT, MPV and histograms for WBC, RBC, PLT

Principles

Electrical impedance method for cell counting and Cyanide - free for hemoglobin

Performance

Parameter	Linearity Range	Precision (CV%)
WBC ($10^3/\mu L$)	0.3 - 99.9	3.0(≥4.0)
RBC ($10^6/\mu L$)	0.2 - 7.99	2.5
HGB (g/dL)	1.0 - 24.99	2.0
MCV (fL)		2.0
PLT (10 ³ /μL)	10 -999	6(≥150)

Sample Volume

Prediluted 20µL Whole Blood 21µL

Throughput

60 samples per hour

Display

Large color touch screen Resolution: 800×600

Carryover

WBC, RBC, HGB≤0.5% PLT≤1.0%

Connectivity

4 USB ports (for external printer, software upgrade, barcode reader, keyboard and mouse), LAN port (1), RS232 (1)

intout

Thermal recorder, 50mm width paper, various printout formats, external printer (optional)

Operating Environment

Temperature: 15°C~30°C Humidity: 30%~85%

Power requirement

AC 100-240V, 50/60±1Hz

Dimensions

16 in(W) x 18 in(H) x 18 in(D)

Configuration

Close Tube Sampling

Weight

62 lbs



BC-3600

Auto Hematology Analyzer

Pleasant Experience in Hematology Testing



PT. MULTIMEDILAB KARYAMANDIRI
MEDICAL & LABORATORY EQUIPMENTS

GP Plaza Lantai 3 Unit 6 Jl. Gelora II No. 01 RT. 01/01, Kelurahan Gelora Kecamatan Tanah Abang, Jakarta Pusat 10270 – INDONESIA Telp. (021) 3972-9191 (hunting). Fax. (021) 3972-9195





BC-3600

Auto Hematology Analyzer

Labs today are facing a multitude of challenges including limited laboratory budgets, increasing requirements for high quality as well as reliable products, a shortage of experienced clinicians and so on. We understand the specific needs of end users, and use them as the foundation for our new solution BC-3600. Complete with an intuitive operation system, convenient data communication interface, excellent performance, BC-3600 is a system solution for satellite labs and clinics.

- CBC+3-DIFF, 16 parameters+3 histograms
- Throughput: 60 samples per hour
- Intuitive operation system with TFT touch screen
- Enhanced performance by proven technologies
- Closed Tube Sampling
- 40,000 results storage with histograms
- High quality QC, calibrators and reagents



User-friendly

User-friendly






Complete Data Communication

Integrated HL7 communication protocol for LIS connection. A wide selection of interface options are available including RS232 for computer connection, USB for QC assay values upload, barcode scanner, and key board connection.






Intelligence and Efficiency

Efficient ZAP and flush method removes clog completely. For Closed Tube model, 3 types of tube adaptors are provided to satisfy individual laboratory needs. With the on-line reminder function, users can conveniently monitor the reagent residual volumes through the software.











Intuitive and Powerful Software

single clicks.

The well organized software interface eases your operation

and gives you easy control of sample results, patient records,